


VENT 1001A-L3140A90-04

Luminaire for pole VENT IP66 LED SMD 35.50W 5770lm(4635lm) CRI80 3000K 95°
410mm Anthracite



The luminaire for vent poles, made of aluminum and anthracite finish, is supplied in two 40W and 75W powers with yields up to 120lm / W (OUTPUT) and with IK66 and IK08 protection degrees that, together with high resistance to corrosion, make it ideal for exterior lighting applications. With a modern and contemporary design, along with high technical specifications, it is presented as a great option to illuminate all types of spaces.

GENERAL DATA

Category	Bollards and columns
Family	Vent
Finish	[04] Anthracite
Location	Outdoor
Installation	Poste
Body material	Aluminum
Diffuser material	Crystal
ETIM class	EC000062
EAN	8433264124168

LIGHT SOURCES AND BEAMS

Sources	LED SMD 35.5W 5770lm(4635lm) 3000K CRI80
Energy efficiency	D (3000K)
Beam	95°


TECHNICAL DATA

Dimensions	Diameter x Height x Pole's base diameter (mm) (mm): 476 x 410 x 60
IP	IP66
IK	08
Protection class	Class I
Frequency	50/60 Hz
Input voltage	110-240V AC V
Output current	1,050 mA
Power factor	0.9
Auxiliary gear	Integrated driver
Auxiliary equipment brand	Inventronics
Operating temperature range	-30 - 50 °C
Lifetime	100,000 h
LED lifetime L	80
LED lifetime B	10
Weight	8.0 Kg
Cable outlets	1
Lead wire length	1,000.0 mm

PHOTOMETRIC DATA

VENT 1001A-L3140A90-04

Luminaire for pole VENT IP66 LED SMD 35.50W 5770lm(4635lm) CRI80 3000K 95°
410mm Anthracite



NOTES

Incorpora válvula depresora para mantener constante la presión y evitar la entrada de humedad.

Corrosion resistance (salt spray: > 1000h)

Type V (symmetrical) optics for landscaped areas, meeting areas, parking areas,...

VENT 1001A-L3140A90-04

Luminaire for pole VENT IP66 LED SMD 35.50W 5770lm(4635lm) CRI80 3000K 95°
410mm Anthracite

RECOMMENDED ACCESSORIES

		<p>B03A-X33X2A-02 Accesorios / Doble conector hasta Ø13mm CONECTORES Black</p>	<p>IP IP68 Protection class Class I</p>
		<p>B03B-X33X2A-02 Accesorios / Triple conector T desde Ø13,5mm CONECTORES Black</p>	<p>IP IP68 Protection class Class I</p>
		<p>C03B-32-39 TopØ60 pole POSTES 3000mm Anodized aluminum</p>	
		<p>C03C-32-39 TopØ60 pole POSTES 3500mm Anodized aluminum</p>	
		<p>C03D-32-39 TopØ60 pole POSTES 4000mm Anodized aluminum</p>	
		<p>C03F-32-39 TopØ60 pole POSTES 5000mm Anodized aluminum</p>	

VENT 1001A-L3140A90-04

Luminaire for pole VENT IP66 LED SMD 35.50W 5770lm(4635lm) CRI80 3000K 95°
410mm Anthracite

COMPLEMENTARY IMAGES

